




Entrance flooring Sheet, tiles, planks and mats

coral[®]

classic | brush | duo | welcome | interior | grip



creating better environments

Forbo
FLOORING SYSTEMS



Keep dirt at the door with a Coral entrance flooring system.

We have been the world leader in textile entrance flooring for over 50 years, so there is nothing we don't know about stopping dirt and moisture coming into your building.

First impressions count.

We all know the feeling that comes with walking on a newly installed, clean floor.

By installing a Coral entrance system, you can ensure the floor and premises continues to look clean and presentable year after year, as well as delivering a safe and hygienic environment for visitors and employees.

There is a lot of time and money spent on the visual appearance of a building. It is often forgotten that this design can only be retained when the floor stays clean and undamaged.

A well designed entrance flooring system can:

- reduce the risk of slip injuries
- prolong the life of the interior floor finish
- reduce the cost of on-going maintenance
- make the entrance look good and inviting
- contribute to an environmentally friendly building through the use of Econyl® 100% regenerated yarns.

The WELL Building Standard® recommends using entrance matting as a key tool to minimise pollutants entering the building.

The Coral collections are designed with our own yarn system that contributes to scraping dirt and wiping off moisture, resulting in an entrance that still looks good, even after years of use. We use the 4R principle for this, Coral;

- Removes soiling
- Retains the soiling in the mat
- Releases soiling while cleaning
- Recovers as new after cleaning

www.forbo-flooring.co.uk/coral


coral[®] brush




- Made with Econyl[®] 100%-regenerated yarns
- Suitable for the toughest commercial use
- Ideal for inside entrance and circulation areas
- Available in Fast Fit, adhesive free format



A good all-rounder that keeps out dirt and moisture




5710 | asphalt grey * LRV 2




5721 | hurricane grey * LRV 3



5774 | biscotti brown LRV 4




5716 | masala brown LRV 5




5714 | shark grey LRV 4




5708 | avocado green LRV 3



5715 | charcoal grey LRV 2



5739 | Byzantine purple LRV 2




5722 | cornflower blue LRV 3




5723 | cardinal red LRV 2




5730 | vulcan black LRV 1



5727 | stratos blue LRV 1



5724 | chocolate brown LRV 3




5736 | cinnamon brown LRV 3

coral[®] classic




- Maximum moisture absorption and scrapes off dirt
- Suitable for the heaviest commercial use
- Ideal for inside entrance and circulation areas
- Available in Fast Fit, adhesive free format


The ultimate moisture absorber



LRV 9




LRV 6




LRV 4




LRV 4




LRV 6



LRV 2




LRV 4




LRV 6



LRV 4



LRV 2



LRV 2



LRV 3

coral[®] duo



9710 | luna pearl



SHEET

ECONYL[®]
ENDLESS POSSIBILITIES




- The ultimate dirt and moisture remover
- Ideal for smaller interior entrances and circulation areas where you need maximum dirt removal and moisture retention




9710 | luna perl

LRV 4




9721 | dark steel

LRV 2




9730 | black diamond

LRV 1




3201 | silver shadow

LRV 3




3205 | blue lagoon

LRV 3



3210 | black magic

LRV 2



3207 | blue velvet

LRV 1

coral[®] welcome



3201 | silver shadow




SHEET



MAT


ECONYL[®]
ENDLESS POSSIBILITIES

- Where design meets environment
- Combines the dirt and moisture removal properties of Coral with the aesthetic of a luxury carpet tile
- Ideal for interior entrances and circulation areas




9714 | Sicilian sand

LRV 4




9708 | green bellagio

LRV 2




9747 | azul imperial

LRV 1




3202 | desperado

LRV 2




3219 | colour purple

LRV 1



3208 | matrix

LRV 2



3206 | volcano

LRV 1



NEW
coral[®] interior

coral[®] classic

coral[®] duo


forbo
FLOORING SYSTEMS


coral[®] grip

open structure  with vinyl backing



6140 | HD  6120 | HD | stone LRV 7



6143 | HD  6123 | MD | wine LRV 5



SHEET



MAT

- Contains granulates for maximum non-slip performance
- Cleans off the worst dirt before it can get inside
- Ideal for areas leading to and from sport and leisure environments

**The robust and ultimate dirt and grit remover
for inside and outside use**



TILE &
PLANKS

- Mix of planks and tiles for ultimate random effect
- Easy and quick installation (no pattern)
- Designed for both entrance and larger circulation zones
- Colour matches with other entrance products
- Suitable for the toughest commercial use

Innovative new modular design



1521 | Alpine peak


LRV 10



1521 | Alpine peak




1530 | midnight shadow




1525 | prairie dusk

LRV 5



1530 | midnight shadow

LRV 1



1515 | storm cloud

LRV 4



1525 | prairie dusk




1515 | storm cloud

coral[®] interior



Coral duo 9714 | Sicilian sand | Coral classic 4764 | taupe | Coral interior 1525 | prairie dusk



1518 | rain forest

LRV 3



1518 | rain forest




1517 | ocean spray




1520 | desert sand

LRV 7



1517 | ocean spray

LRV 2



1513 | savanna sunset

LRV 1



1520 | desert sand



1513 | savanna sunset





Coral technical specifications

		Coral Classic	Coral Brush	Coral Duo	Coral Welcome	Coral Interior	Coral Grip HD
	Area of use	commercial heavy	commercial heavy	commercial heavy	commercial heavy	commercial heavy	commercial heavy
	Colours	12	14	6	8	8	4
	Design	multi coloured	plain coloured	ribbed	multi-coloured linear	random pattern of linear and plain coloured	3-dimensional interconnected monofilaments
	Total thickness ISO 1765	approx. 9mm / Fast Fit tile approx. 10 mm	approx. 9mm / Fast Fit tile approx. 10 mm	approx. 9 mm	approx. 9 mm	approx. 10 mm	open structure approx. 16 mm, with backing approx. 17 mm
	Available widths rolls with 2.5 cm edge each side	105 cm, 155 cm, 205 cm	105 cm, 155 cm, 205 cm	205 cm	205 cm		122 cm (open), 127 cm (backed)
	Available length rolls	27.5 metre	27.5 metre	27.5 metre	27.5 metre		approx. 10 metre
	Available in tiles	50x50 cm / 12 per box / 3 m²	50x50 cm / 12 per box / 3 m²			50x50 cm & 100x25 cm / 6 tiles & 6 planks per box (3m²)	
	Fast Fit tile dimensions	50x50 cm / 12 per box / 3 m²	50x50 cm / 12 per box / 3 m²				
	Mat dimensions with 2.5 cm edge each side	55x90 cm, 90x155 cm 135x205 cm, 205x300 cm	55x90 cm, 90x155 cm 135x205 cm, 205x300 cm		105x155 cm		60x90 cm (open)
	Sound absorption ISO 354	αw = 0.25 (H) Fast Fit Tiles	αw = 0.25 (H) Fast Fit Tiles			αw = 0.20 (H)	
	Reduction impact noise ISO 10140-3	ΔLw 29 dB (Fast Fit tiles)	ΔLw 29 dB (Fast Fit tiles)			ΔLw 28 dB	
	Colour fastness to light EN ISO 105/B02	7-8	≥ 5	≥ 5	7	≥ 5	7
	Colour fastness ratings						
	Rubbing EN ISO 105/X12	4-5	5	4-5	5	4-5	4-5
	Water EN ISO 105/E01	4-5	4-5	4-5	4-5	5	5
	Seawater EN ISO 105/E02	4-5	4-5	5	4-5	4-5	5
	Waterstains EN 1307 annex G	4-5	5	5	5	5	5
	Shampoo BS 1006	4-5	4-5	4-5	4-5	4-5	5
	Organic solvents EN ISO 105/X05	4-5	4-5	4-5	4-5	4-5	4-5
	Manufacturing method	tufted 5/32"cut pile	tufted 5/32"cut pile	tufted 5/32"cut pile	tufted 5/32"cut pile	tufted 5/32"cut pile	non woven scraping mat with embossing
	Pile material	solution dyed polyamide	regenerated ECONYL® polyamide	regenerated ECONYL® polyamide solution dyed polyamide	regenerated ECONYL® polyamide	regenerated ECONYL® polyamide solution dyed polyamide	solution dyed vinyl with anti-slip granulate particles
	Tuft base	non-woven	non-woven	non-woven	100% recycled non-woven	non-woven	
	Backing phthalate free vinyl	EVERFORT vinyl	EVERFORT vinyl	EVERFORT vinyl	EVERFORT vinyl	EVERFORT vinyl	open structure or with EVERFORT vinyl backing
	Total weight ISO 8543	approx. 4000 g/m²	approx. 4050 g/m²	approx. 3800 g/m²	approx. 3950 g/m²		approx. 5500 g/m² (open) approx. 8100 g/m² (backed)
	Total weight tiles ISO 8543	approx. 4100 g/m² (Fast Flooring approx. 5000 g/m²)	approx. 4100 g/m² (Fast Flooring approx. 5000 g/m²)			approx. 4150 g/m²	
	Pile installation weight ISO 8543	approx. 870 g/m²	approx. 920 g/m²	approx. 670 g/m²	approx. 750 g/m²	approx. 970 g/m²	
	Pile thickness ISO 1766	approx. 7 mm	approx. 7 mm	approx. 6 mm	approx. 6,3 mm	approx. 6 mm	
	Pile density ISO 8543	0.100 g/cm³	0.105 g/cm³	0.095 g/cm³	0.111 g/cm³	0.100 g/cm³	
	Number of tufts ISO 1763	approx. 61,500/m²	approx. 58,000/m²	approx. 32,000/m²	approx. 79,300/m²	approx. 58,000/m²	

All Coral products meet the requirements set by EN 14041: 2004, excluding loose-laid mats

	DoP	1300147-DoP-004 1300150-DoP-107 (tiles)	1300147-DoP-004 1300150-DoP-107 (tiles)	1300147-DoP-004	1300147-DoP-004	1300150-DoP-107	1300118-DoP-004
	Reaction to fire EN 13501-1	B _{f1} ≤1, G, NCS	B _{f1} ≤1, G, NCS	B _{f1} ≤1, G, NCS	B _{f1} ≤1, G, NCS	B _{f1} ≤1, G, NCS	B _{f1} ≤1, G, NCS (with backing)
	Slip resistance EN 13893	μ > 0.30	μ > 0.30	μ > 0.30	μ > 0.30	μ > 0.30	μ > 0.30
	Body voltage ISO 6356	≤ 2 kV	≤ 2 kV	≤ 2 kV	≤ 2 kV	≤ 2 kV	≤ 2 kV

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.
The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.



UK

Forbo Flooring UK Limited
High Holborn Road, Ripley
Derbyshire DE5 3NT

London EC1 showroom

79 St John Street, Clerkenwell
London EC1M 4NR
Tel: 0207 553 9300

For commercial enquiries:

If calling from the North,
Midlands, London & South East
Tel: 0800 0282 162

If calling from Scotland & South West
Tel: 0800 0935 258

Nuway enquiries:

Tel: 01773 740 688

Residential enquiries:

Tel: 0800 0935 846

Email: info.flooring.uk@forbo.com
www.forbo-flooring.co.uk

Samples:

Tel: 0800 731 2369
samples.uk@forbo.com

Find us on



Ireland

Forbo Ireland Ltd
2 Deansgrange Business Park
Blackrock
Co Dublin

Tel: 00353 1 2898 898
Fax: 00353 1 2898 177
Email: info.ireland@forbo.com
www.forbo-flooring.ie

Registered office:

Forbo Flooring UK Limited
High Holborn Road, Ripley
Derbyshire DE5 3NT
Registered in England: No 9200318



Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this samplebook are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, expressed or implied in respect of the information, content, materials or products displayed in this samplebook and does not represent that the information is accurate, complete or current and you are advised to visit our website at www.forbo-flooring.co.uk for up-to-date details or corrections to such contents.



FLOORING SYSTEMS